

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A connector device for optically coupling an optical fiber to another optical component to deliver light to or receive light from it, wherein the positional relationship between the end of the said optical fiber and the said other optical component is determined by means for locating the end of the said optical fiber in a predetermined position both parallel to and transverse the length of the fiber with respect to the said optical component.
2. (Original) A connector device according to claim 1 for coupling non-aligned (as herein defined) optical fibers, in which light is directed from the said optical fiber to another by a reflector and the positional relationship between the ends of the optical fibers and the reflector is determined by means for locating the end of each optical fiber to be coupled in a predetermined position both parallel to and transverse the length of the fiber.
3. (Original) A connector device for coupling non-aligned optical fibers as claimed in Claim 2, in which there are provided collimating lenses in predetermined positions with respect to the reflector and to the means for locating the ends of the optical fibers in the said predetermined positions whereby to direct light from one fiber to another via the reflector.
4. (Original) A connector device as claimed in Claim 3, in which the said collimating lenses are integrally formed with the said means for locating the ends of the optical fibers to be coupled, there being provided means for determining the relative position of the reflector and the said means for locating the ends of the optical fibers to be coupled, the latter being adapted to locate the optical fiber at a determined distance in relation to the focal length of the lenses.
5. (Original) A connector device as claimed in Claim 3, in which the reflector is formed integrally with the said collimating lenses.

6. (Original) A connector device as claimed in Claim 4, in which the said means for locating the ends of the optical fibers to be coupled comprise a locating member having openings for receiving the ends of the optical fibers to be coupled and means for determining the relative position and orientation of the said locating member with respect to the reflector.
7. (Original) A connector device as claimed in Claim 6, in which the means for determining the relative position and orientation of the locating member with respect to the reflector comprise co-operating form-engagement members on or carried by the said reflector and the said locating member.
8. (Original) A connector device as claimed in Claim 6, in which the said locating member has means for securing it in a predetermined fixed spaced relationship with respect to the reflector.
9. (Original) A connector device as claimed in Claim 1, in which the reflector comprises a generally prismatic element having at least one reflector surface at which reflection takes place by total internal reflection.
10. (Original) A connector device as claimed in Claim 9, in which the reflector prism has two reflector surfaces orthogonal to one another.
11. (Original) A connector device as claimed in Claim 9, in which there are provided collimating lenses in predetermined positions with respect to the reflector and to the means for locating the ends of the optical fibers in the said predetermined positions whereby to direct light from one fiber to another via the reflector, the said collimator lenses being formed integrally with the said reflector prism.
12. (Original) A connector device as claimed in Claim 9, in which the collimator lenses are formed on the locating member or on an intermediate base plate member between the reflector and the said locating member.

13. (Original) A connector device as claimed in any of Claims 12, in which the said reflector surface is metallized to improve reflectivity thereof.

14. (Original) A connector device as claimed in Claim 13, in which the said reflector surface is coated with an aluminum, gold or other metal layer acting to improve reflection from the surface.

15. (Original) A connector device as claimed in Claim 9, in which the reflector surface is formed or associated with a diffraction grating.

16. (Original) A connector device as claimed in Claim 2, in which the reflector is a mirror coated on a front or rear surface thereof.

17. (Original) A connector device as claimed in Claim 3, in which the lenses are cylindrical lenses.

18. (Original) A connector device as claimed in Claim 3, in which the lenses are aspheric lenses.

19. (Original) A connector device as claimed in Claim 2, in which the collimator lenses are formed by irradiation of selected regions of a body of polymer material, followed by a treatment including selective exposure to a monomer of the same material at or above a critical temperature at which the monomer diffuses into the irradiated regions of the polymer.

20. (Original) A connector device as claimed in Claim 1, in which the means for locating the ends of the optical fibers to be coupled comprises means for receiving and locating a plurality of input fibers and a plurality of exit fibers.

21-29. (Cancelled)

30. (Original) A connector device for non-aligned (as herein defined) optical fibers substantially as hereinafter described with reference to, and as shown in, the accompanying drawings.

31. (Original) A connector device for coupling non-contacting optical fibers, comprising at least one lens and means for locating the ends of the optical fibers to be coupled in a predetermined positional relationship with respect to the said lens, whereby to direct light leaving one of the optical fibers substantially entirely into the or an other optical fiber.

32. (Original) A connector device as claimed in Claim 31, in which the said means for locating the ends of the optical fibers in a predetermined positional relationship with respect to the lens comprise at least one alignment plate having openings for receiving the ends of the fibers and locating them in a predetermined position with respect to the said lens.

33. (Original) A connector device as claimed in Claim 32, in which the said lens is integrally formed with a said alignment plate.

34. (Original) A connector device as claimed in Claim 33, in which there are two such alignment plates each having one or more lens integrally formed therewith.

35. (Original) A connector device as claimed in any of Claims 32, in which the opening or openings in the or each alignment plate are tapered.

36. (Original) A connector device as claimed in Claim 33, in which the or each opening in the or each alignment plate is a through hole and the position of the end face of the optical fiber is determined by a transparent stop plate against which the end face of the or an optical fiber is contacted upon formation of the connection.

37. (Original) A connector device for coupling optical fibers, in which light is directed from one fiber to another by an optical component or system other than the fibers themselves, in which the positional relationship between the ends of the optical fibers and the said optical

component is determined by means for locating the end of each optical fiber to be coupled in a predetermined position both parallel to and transverse the length of the fiber.

38. (Original) A connector device as claimed in Claim 37, in which the said means for determining the positional relationship between the ends of the optical fibers and the said optical component or systems comprises at least one alignment plate having openings in predetermined positions for receiving the ends of optical fibers.

39. (Original) A connector device as claimed in Claim 38 in which the said optical component or system comprises or includes at least one lens formed integrally with the said alignment plate or with another part of the said optical system.

40. (Original) A connector device for coupling optical fibers, in which light exiting one fiber is directed to another by optical transmission means outside the fibers in the form of one or more lenses located in a fixed position with respect to fiber end locating means of the connector.

41. (Original) A connector device for coupling optical fibers, as claimed in Claim 40, in which the fiber end locating means comprise openings in an alignment plate for receiving the ends of the fibers, the lens or lenses also being formed integrally on the alignment plate.

42. (Original) A connector device according to claim 41, for optically coupling an optical fiber to another optical component other than an optical fiber whereby to deliver light to or receive light from it, in which the positional relationship between the end of the optical fiber and the said other optical component is determined by means for locating the end of the said optical fiber in a predetermined position both parallel to and transverse the length of the fiber with respect to the said optical component.

43. (Original) A connection device as claimed in Claim 42, in which there is provided a lens in the path of light between the end of the said optical fiber and the other optical component.

44. (Original) A connector device as claimed in Claim 43, in which the said lens is one formed by irradiation of selected regions of a body of polymer material followed by a treatment including selective exposure to a monomer at or above a critical temperature at which the monomer diffuses into the irradiated regions of the polymer.

45. (Original) A connector device as claimed in Claim 42, in which the means for locating the end of the fiber is formed by irradiation of a selected region of a body of polymer material, followed by a treatment including selective exposure to a monomer at or above a critical temperature at which the monomer diffuses into the irradiation regions of the polymer, and thereafter a selective etching of the thus-treated region to result in an accurately formed opening for receiving the end of the optical fiber whereby to locate it in the said predetermined position.

46. (Original) A connector device as claimed in Claim 42, in which the said other optical component is a light source.

47. (Original) A connector device as claimed in Claim 42, in which the said other optical component is a photo detector.

48-49. (Cancelled)